

**MATERIAL SAFETY DATA SHEET****Warren Unilube, Inc.**

Address: 915 E. Jefferson Ave.  
West Memphis, AR 72301

Phone: (800) 428-9284

Chemtrec Number:  
Domestic: 800-424-9300  
International: 703-527-3887

**PRODUCT IDENTIFICATION**

Trade Name: Coastal Premium GL-5 75W-90, 80W-90, 85W-140  
Outboard Gear Lube 80W-90 Date Revised: July 28, 2008

Synonyms/Product Code: N. A.  
Chemical Name: Petroleum Mineral Oil  
Family Description: A complex combination of hydrocarbons from a petroleum fraction obtained by solvent crystallization plus additives.  
Shipping Information: DOT Hazard Class-Not Applicable.

NFPA Codes: Health=0, Flammability=1, Reactivity=0

**COMPOSITION**

<u>Product</u>	<u>CAS Number</u>	<u>Wt%</u>	<u>Occupational Exposure Limits*</u>			<u>Units</u>
			<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other</u>	
Coastal Premium GL-5 75w90, 80w90, 85w140 Outboard Gear Lube 80w90	Mixture	100	N.A.	N.A.	N.A.	N.A.
<b><u>Ingredient(s):</u></b>						
Solvent Dewaxed Heavy Paraffinic Petroleum Distillate	64742-65-0	>85	5	5	10 STEL	mg/m <sup>3</sup> **
Solvent Refined Residual Oil	64742-62-7	7	5	5	10 STEL	mg/m <sup>3</sup> **
Additives containing polymers	N.A.	5-8	N.A.	N.A.	N.A.	N.A.

This product contains <3% (w/w) DMSO extract, according to IP346.

\* = 8-Hr. TWA unless otherwise specified.  
\*\* = As mineral oil mist  
N.A. = Not Available  
STEL = Short Term Exposure Limit; 15 minutes.

**PHYSICAL AND CHEMICAL PROPERTIES**

Boiling Point 760 mmHg:	N.A.	Melting Point:	N.A.
Vapor Pressure mmHg @ 100F:	N.A.	Vapor Density (air=1):	N.A.
Solubility in H <sub>2</sub> O %:	Nil	pH:	N.A.
Specific Gravity (H <sub>2</sub> O):	0.9013	Evaporation Rate	
% Volatile by Volume:	N.A.	(ethyl ether=1):	N.A.
Viscosity (method,temp):	14 cSt @100C	Odor:	Slight hydrocarbon odor
Appearance: Light amber liquid			

N.A. = Not Available

This product has a concentration of DMSO extractables below 3.0 percent, when measured by method IP346.

**FIRE AND EXPLOSION DATA**

Flash Point:	500°F	
Flammable Limits in Air % by Vol.:	Lower: N.A.	Upper: N.A.
Autoignition Temperature:	N.A.	
Extinguishing Media:	Dry chemical, foam, carbon dioxide, or water spray.	
Special Fire Fighting Procedure:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.	
Unusual Fire or Explosion Hazard:	May ignite when sufficient heat is applied.	

**REACTIVITY DATA**

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid/Incompatibility:	Strong oxidizing agents, heat, spark, flame and build-up of static electricity.
Hazardous Decomposition Products:	Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and combustion products of sulfur and nitrogen.

**HEALTH HAZARD DATA**

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No	IARC Monographs: No	OSHA Regulated: No
Occupational Exposure Limits:	See <u>COMPOSITION</u> section.	

**Effects of Overexposure:****Acute:**

**Eyes:** Mildly irritating to the eyes. Injury to the eye may occur if product is not removed promptly.

**Skin:** May cause slight skin irritation.

**Inhalation:** The inhalation hazards of the components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits. Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation, drowsiness, dizziness, headache and nausea.

<b>Ingestion:</b>	Ingestion of large amounts may cause headache, drowsiness, nausea, vomiting or diarrhea. Aspiration hazard if vomiting occurs.
<b><u>Chronic:</u></b>	Frequent or prolonged contact may cause skin irritation. Repeated excessive exposure to mists may cause pulmonary irritation or chronic bronchitis.
<b>Additional Medical and Toxicological Information:</b>	May aggravate pre-existing dermatitis. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of used oils in experimental animals.

### **EMERGENCY FIRST AID PROCEDURES**

<b>Eye Contact:</b>	Flush thoroughly with water for at least 15 minutes, including under the eyelids. Contact a physician immediately, preferably an Ophthalmologist. Speed and thoroughness in rinsing eyes are important to avoid permanent injury.
<b>Skin Contact:</b>	Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical attention.
<b>Inhalation:</b>	Remove to fresh air. If breathing has stopped, apply artificial respiration. Get immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head lower than hips to prevent aspiration.

### **SPECIAL PROTECTION INFORMATION**

<b>Eye Protection:</b>	Remove contact lenses and wear chemical safety goggles where contact with liquid or mist may occur.
<b>Skin Protection:</b>	Wear impervious gloves when contact with skin may occur. Use face shield where splashing may occur. Wash with soap and water before eating, drinking or smoking. Launder contaminated clothing before reuse.
<b>Inhalation:</b>	Use approved respiratory protective equipment for cleaning large spills or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels.
<b>Ventilation:</b>	Provide adequate general and local exhaust ventilation: (1) to keep mist or vapors below occupational exposure levels; and (2) to prevent the formation of an oxygen deficient atmosphere, particularly in a confined space area.

### **SPILL OR LEAK AND DISPOSAL PROCEDURES**

<b>Spill Procedures:</b>	Remove sources of heat or ignition including internal combustion engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with an absorbent. Use approved respirator where occupational exposure limits may be exceeded.
<b>Waste Disposal:</b>	Dispose of through a licensed waste disposal company. Follow federal, state and local regulations.

**SPECIAL PRECAUTIONS AND COMMENTS****Storage Requirements:**

Store in tightly closed containers in a dry, cool place, away from sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment and equip with self closing valves, pressure vacuum bungs and flame arrestors.

**SARA TITLE III INFORMATION****Section 311/312 Hazard Categorization**

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>
X	X			

**SARA Hazardous Substances**

<u>Ingredient</u>	<u>CAS No.</u>	<u>%, wt</u>	<u>Sec 313</u>	<u>Sec 302</u>	<u>RQ, lb</u>	<u>TPQ, lb</u>
None						

Key: Sec 313 = Toxic Chemicals, Section 313  
 Sec 302 = Extremely Hazardous Substances (EHS)  
 RQ = Reportable Quantity of EHS  
 TPQ = Threshold Planning Quantity of EHS

**CALIFORNIA PROPOSITION 65 WARNING**

Chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.