


**SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** KILZ® Upshot Primer Sealer - Aerosol  
**MSDS Manufacturer Number:** 10007  
**Manufacturer Name:** Masterchem Industries LLC  
**Address:** 3135 Old Highway M  
 Imperial, MO 63052-2834  
**General Phone Number:** (636) 942-2510  
**General Fax Number:** (636) 942-3663  
**Customer Service Phone Number:** (800) 325-3552  
**CHEMTREC:** For emergencies in the US, call CHEMTREC: 800-424-9300  
**Canutec:** In Canada, call CANUTEC: (613) 996-6666 (call collect)  
**MSDS Creation Date:** June 26, 2006  
**MSDS Revision Date:** July 06, 2009  
**MSDS Format:** According to ANSI Z400.1-2004



HMS

Health Hazard	1
Fire Hazard	3
Reactivity	0
Personal Protection	x

\* Chronic Health Effects

**SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS#	Ingredient Percent
Titanium dioxide	13463-67-7	5 - 10 by weight
Talc, Magnesium silicate hydrate	14807-96-6	1 - 5 by weight
Nonanes	No data	5 - 10 by weight
Aliphatic Hydrocarbon	64742-49-0	5 - 10 by weight
Rutile	1317-80-2	1 - 5 by weight
Silicate, mica	12001-26-2	5 - 10 by weight
Undisclosed/Proprietary	No data	10 - 30 by weight
Octanes, all Isomers	No data	5 - 10 by weight
Non-hazardous ingredients		5 - 10 by weight
Acetone	67-64-1	10 - 30 by weight
n-butane	106-97-8	5 - 10 by weight
Propane	74-98-6	10 - 30 by weight
Isobutane	75-28-5	1 - 5 by weight

**SECTION 3 - HAZARDS IDENTIFICATION**

**Emergency Overview:** Extremely flammable aerosol. Irritant. Contents under pressure.  
**Potential Health Effects:**  
     **Eye:** May cause irritation.  
     **Skin:** May cause irritation.  
     **Inhalation:** Prolonged or excessive inhalation may cause respiratory tract irritation.  
     **Ingestion:** Harmful if swallowed. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation.  
**Chronic Health Effects:** Prolonged or repeated contact can result in defatting and drying of the skin, which may result in skin irritation and dermatitis (rash). Repeated or prolonged inhalation may cause toxic effects.  
**Signs/Symptoms:** Overexposure can cause headaches, dizziness, nausea, and vomiting.  
**Target Organs:** Eyes, Skin, Respiratory system, Digestive system, Central nervous system, Kidney.  
**Aggravation of Pre-Existing Conditions:** May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

**SECTION 4 - FIRST AID MEASURES**

**Eye Contact:** Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.  
**Skin Contact:** Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

## SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:	Extremely flammable aerosol. Contents are under pressure. Will release flammable vapors at well below ambient temperatures and readily form flammable mixtures with air. It will burn in the open and may be explosive in confined spaces.
Flash Point:	-156°F (-104°C)
Lower Flammable/Explosive Limit:	0.8%
Upper Flammable/Explosive Limit:	12.8%
Fire Fighting Instructions:	Flammable. Cool fire-exposed containers using water spray.
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.

### NFPA Ratings:

NFPA Health:	1
NFPA Flammability:	4
NFPA Reactivity:	0
NFPA Other:	NA

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Use proper personal protective equipment as listed in section 8.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Remove all sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal.

## SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Work Practices:	To reduce potential for static discharge, bond and ground containers when transferring material.
Special Handling Procedures:	Do not reuse containers without proper cleaning or reconditioning.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

### Titanium dioxide:

Guideline ACGIH:	TLV-TWA: 10 mg/m <sup>3</sup>
Guideline OSHA:	OSHA-TWA: 15 mg/m <sup>3</sup>

**Talc, Magnesium silicate hydrate:**

Guideline ACGIH: TLV-TWA: 2 mg/m3 (Respirable)  
 Guideline OSHA: OSHA-TWA: 20 mg/m3

**Silicate, mica:**

Guideline ACGIH: TLV-TWA: 3 mg/m3 (Respirable)  
 Guideline OSHA: OSHA-TWA: 20 mg/m3

**Undisclosed/Proprietary:**

Guideline ACGIH: TLV-TWA: 300 ppm

**Acetone:**

Guideline ACGIH: TLV-TWA: 500 ppm  
 TLV-STEL: 750 ppm  
 Guideline OSHA: OSHA-TWA: 1000 ppm

**n-butane:**

Guideline ACGIH: TLV-TWA: 1000 ppm

**Propane:**

Guideline ACGIH: TLV-TWA: 1000 ppm  
 Guideline OSHA: OSHA-TWA: 1000 ppm

**Isobutane:**

Guideline ACGIH: TLV-TWA: 1000 ppm

**SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES**

Physical State Appearance: Liquid.  
 Boiling Point: No Data  
 Melting Point: No Data  
 Density: 10 - 12 Lbs./gal.  
 Vapor Density: Greater than 1 (Air = 1).  
 pH: No Data  
 Molecular Formula: Mixture  
 Molecular Weight: Mixture  
 Flash Point: -156°F (-104°C)

**SECTION 10 - STABILITY and REACTIVITY**

Chemical Stability: Stable under normal temperatures and pressures.  
 Hazardous Polymerization: Not reported.  
 Conditions to Avoid: Heat, flames, ignition sources, and sparks. Incompatible materials. Freezing or temperatures below 32 deg. F.  
 Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

**SECTION 11 - TOXICOLOGICAL INFORMATION****Titanium dioxide:**

RTECS Number: XR2275000  
 Skin: Skin - Rabbit; Standard Draize Test. : 300 ug/3D; (Intermittent) mild. (RTECS)  
 Ingestion: Ingestion - Rat TDLo: 60 gm/kg; Gastrointestinal - hypermotility, diarrhea  
 Gastrointestinal - other changes. (RTECS)  
 Carcinogenicity: IARC: Group 2B: Possibly carcinogenic to humans.

**Talc, Magnesium silicate hydrate:**

RTECS Number: WW2710000  
 Carcinogenicity: IARC: Group 3: Unclassifiable as to carcinogenicity to humans.

**Rutile:**

RTECS Number: VM2940000

**Silicate, mica:**

RTECS Number: VV8760000

**Undisclosed/Proprietary:**

RTECS Number: OI6180000  
 Eye: Eye's - Human: 880 ppm/15M; No effects reported. (RTECS)

**Acetone:**

Eye: Eye - Rabbit; Standard Draize Test. : 10 uL - mild (RTECS)  
 Skin: Skin - Guinea pig; LD50: >9400 uL/kg - Details of toxic effects not reported other than lethal dose value.. (RTECS)  
 Inhalation: Inhalation - Rat LC50: 50100 mg/m3/8H - [Details of toxic effects not reported other than lethal dose value.  
 Inhalation - Mouse LC50: 44 gm/m3/4H - Details of toxic effects not reported other than lethal dose value.. (RTECS)  
 Ingestion: Ingestion - Rat LD50: 5800 mg/kg - Behavioral - altered sleep time (including change in righting reflex) Behavioral - tremor  
 Ingestion - Mouse LD50: 3 gm/kg - [Details of toxic effects not reported other than lethal dose value.. (RTECS)

**n-butane:**

RTECS Number: EJ4200000  
 Inhalation: Ingestion - Rat LC50: 658000 mg/m3/4H - [Details of toxic effects not reported other than lethal dose value.] (RTECS)

**Isobutane :**

Inhalation: Inhalation - Rat LC50: 570,000 ppm/15M - [Behavioral - tremor Behavioral - convulsions or effect on seizure threshold Lungs, Thorax, or Respiration - respiratory depression) (RTECS)

**SECTION 12 - ECOLOGICAL INFORMATION**

Ecotoxicity: No ecotoxicity data was found for the product.  
 Environmental Fate: No environmental information found for this product.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container. Do not store unused product inside the home. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency.

**SECTION 14 - TRANSPORT INFORMATION**

DOT Shipping Name: Aerosol flammable  
 DOT UN Number: UN1950  
 DOT Hazard Class: 2.1  
 DOT Packing Group: III

**SECTION 15 - REGULATORY INFORMATION**

California PROP 65: WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

**Titanium dioxide :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the New Jersey State Right to Know List.  
 Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**Talc, Magnesium silicate hydrate :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the New Jersey State Right to Know List.  
 Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**Aliphatic Hydrocarbon :**

TSCA Inventory Status: Listed  
 Canada DSL: Listed

**Rutile :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**Silicate, mica :**

TSCA Inventory Status: Not listed  
 State Regulations: Listed in the New Jersey State Right to Know List.  
 Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**Undisclosed/Proprietary :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the New Jersey State Right to Know List.  
 Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**Non-hazardous Ingredients :**

TSCA Inventory Status: Contains calcium carbonate (CAS:1317-65-3), which is listed in the TSCA Inventory.

**Acetone :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the Pennsylvania State Hazardous Substances List.  
 Canada DSL: Listed

**n-butane :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the Pennsylvania State Hazardous Substances List.  
 Listed in the New Jersey State Right to Know List.  
 Canada DSL: Listed

**Propane :**

TSCA Inventory Status: Listed  
 State Regulations: Listed in the Pennsylvania State Hazardous Substances List.

Canada DSL: Listed In the New Jersey State Right to Know List.  
Listed  
Isobutane:  
TSCA Inventory Status: Listed  
State Regulations: Listed In the Pennsylvania State Hazardous Substances List.  
Listed In the New Jersey State Right to Know List..  
Canada DSL: Listed

**SECTION 16 - ADDITIONAL INFORMATION**

HMIS Health Hazard: 1  
HMIS Fire Hazard: 3  
HMIS Reactivity: 0  
HMIS Personal Protection: x  
MSDS Creation Date: June 26, 2006  
MSDS Revision Date: July 06, 2009  
MSDS Revision Notes: Quarterly formula update  
MSDS Author: Actio Corporation  
Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.  
Trademark: The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved.

Copyright© 1996-2010 Actio Software Corporation. All Rights Reserved.